


VLF-200

Separation and filter geotextile, 2x175m
#320205



Technical Data Sheet

■ Green up the roof!

	CE marked, nonwoven geotextile made of UV stabilized polypropylene fibers, with a surface weight of 200 g/m ² for filtering and separating purposes on intensive green roofs. thickness: 1.9 mm; tensile strength MD: 16 kN/m; tensile strength CMD: 16 kN/m; Static puncture test (CBR): 2350 N; Dynamic perforation test (Cone drop test): 22 mm; water permeability 115 l/m ² s; Characteristic opening size: 0.10 mm; GRK 3; packaging: 350 m ² /roll; brutto weight: 80 kg/roll; Colour: grey; Laying with an overlap of 10 cm.	
	Dim.	VLF-200
Surface weight	g/m ²	200
Thickness	mm	1.9
Tensile strength MD	kN/m	16
Tensile strength CMD	kN/m	16
Elongation MD	%	95
Elongation CMD	%	46
CBR puncture	N	2350
Cone drop test	mm	22
Characteristic opening size O90	mm	0.1
Water permeability normal to the plane V _{H50}	l/m ² s	115

Reviewed: 2017-03-23

Specifications are subject to change without notice.

APP Kft.

H-9028 Győr, Fehérvári út 75.
Email: info@diadem.com; Web: www.diadem.com