

VLU-300


Technical protection fleece for extensive green roofs

#320416



Technical Data Sheet

■ Green up the roof!

	Rot-proof mechanical protection layer thermally treated on both sides made of 100 % synthetic fibres. Water permeability: 95 mm/s; Surface weight: 300 g/m ² ; tensile strength MD: 2.7 kN/m; tensile strength CMD: 3.7 kN/m; Static puncture test (CBR): 1 kN; Characteristic opening size: 0.134 mm; Robustness class: GRK 2; colour: Multicolour; packaging: 100 m ² /roll; packaging weight: 30 kg/roll. Laying with an overlap of 10 cm.	
	Dim.	VLU-300
Surface weight	g/m ²	300
Thickness	mm	1.8
Tensile strength MD	kN/m	2.7
Tensile strength CMD	kN/m	3.7
Elongation MD	%	75-90
Elongation CMD	%	65-85
Static puncture test (CBR)	kN	1
Characteristic opening size O90	mm	0.13
Water permeability	mm/s	95
Robustness class	GRK	2
Method of production		heat treated on both sides

Reviewed: 2015-07-03 11:47:41

Specifications are subject to change without notice.

APP Kft.

H-9028 Győr, Fehérvári út 75.

Email: info@diadem.com; Web: www.diadem.com