

"Walk- and Driveway" with Stabilodrain® SD 30

Detail:

System Build-Up

System build-up

1.1 Paving, e.g. concrete pavers

Depth: \geq 100 mm for cars up to 3 t

≥ 120 mm for lorries up to16 t

≥ 140 mm for lorries exceeding 16 t

1.2 Bedding layer, stone chippings, poor in lime, 30-50 mm

1.3 Compacted base layer, e.g. gravel, poor in lime

Depth: \geq 150 mm for cars up to 3 t

≥ 200 mm for lorries up to16 t

≥ 250 mm for lorries exceeding 16 t

1.4 Filter Sheet PV

1.5 Stabilodrain® SD 30, filled with stone chippings (see 1.2)

1.6 Filter Sheet PV

1.7 Roof construction with suitable water proofing

Note:

The detailed solution shown here refers mainly to the ZinCo System Build-up. The roof construction itself as well as any other constructions are shown schematically and must be planned according to the relevant standards and guidelines.

Project:

-

 Version:
 Reviewed:
 Scale:
 Size:

 28.11.2018 PBi/ EVo
 none
 A 4

SysFahr G+F SD30 Fd0.dwg

Authorized by ZinCo GmbH, Lise-Meitner-Str. 2, 72622 Nuertingen/ Germany; Tel: ++49/7022-6003-0 info@zinco-greenroof.com; www.zinco-greenroof.com

ZinCo

Subject to technical alterations and printing errors.