

## "Driveway" with Fixodrive® FX 50

Detail:

System build-up

## System build-up

1.1 Paving, e.g. concrete pavers

Depth:  $\geq$  100 mm for cars up to 3 t

≥ 120 mm for lorries up to 16 t

≥ 140 mm for lorries exceeding 16 t

1.2 Bedding layer, poor in lime, 30-50 mm

1.3 Gravel base layer, poor in lime

Depth:  $\geq$  150 mm for cars up to 3 t

≥ 200 mm for lorries up to 16 t

≥ 250 mm for lorries exceeding 16 t

1.4 Fixodrive® FX 50 with attached filter sheet

1.5 Filter Sheet PV

1.6 Roof construction with root resistant waterproofing

## Note:

The detailed solution shown here refers mainly to the ZinCo System Build-up. The roof construction itself as well as any other constructions are shown schematically and must be planned according to the relevant standards and guidelines.

## Project:

1

 Version:
 Reviewed:
 Scale:
 Size:

 29.11.2018 EVo / JGI
 none
 A 4

Sys\_G+F\_FX50\_Fd1.dwg

Authorized by ZinCo GmbH, Lise-Meitner-Str. 2, 72622 Nuertingen/ Germany; Tel: ++49/7022-6003-0 info@zinco-greenroof.com; www.zinco-greenroof.com

ZinCo

Subject to technical alterations and printing errors.