

"Driveway for Lorries" with Elastodrain® EL 202

Detail:

System Build-Up

System build-up

1.1 Paving, e.g. concrete pavers

Depth: \geq 120 mm for lorries up to 16 t

≥ 140 mm for lorries exceeding 16 t

1.2 Beddign layer, poor in lime, 30-50 mm

1.3 Gravel base layer, poor in lime

Depth: ≥ 150 mm for lorries up to 16 t

≥ 150 mm for lorries exceeding 16 t

1.4 Filter Sheet PV

1.5 Elastodrain® EL 202

1.6 Slip Sheet TGF 20 (2 layers)

1.7 Roof construction with root resistant waterproofing

Note:

The detailed solution shown here refers mainly to the ZinCo System Build-up. The roof construction itself as well as any other constructions are shown schematically and must be planned according to the relevant standards and guidelines.

Project:

 Version:
 Reviewed:
 Scale:
 Size:

 23.11.2018 EVo/ JGI
 none
 A 4

Sys_G+F_LKW_EL202_Fd1.dwg

Authorized by ZinCo GmbH, Lise-Meitner-Str. 2, 72622 Nuertingen/ Germany; Tel: ++49/7022-6003-0 info@zinco-greenroof.com; www.zinco-greenroof.com



Subject to technical alterations and printing errors.