

- 2.1 Balcony and Terrace Channel BTR
- 2.2 Locking Disc
- 2.3 Cantilever Art Support
- 2.4 Joint Spacer

"Walkway" with Elefeet[®]

Detail:

Wall Connection with Channel

System build-up

- 1.1 Concrete or natural stone slabs, $d \ge 40 \text{ mm}^*$)
- 1.2 Elefeet® Pedestals, height adjustable
 (The integrated joint spacer partly need to be removed and if necessary, be replaced by additional joint spacers.)
- 1.3 ES 30 (additional separating layer, e.g. TGF 20 Elastosafe or TGV 21 in case of material incompatibility, where applicable)
- 1.4 Suitable roof construction with root resistant waterproofing (with pressure resistant insulation, if required)
- *) Other slab heights are possible if approved by the manufacturer.

 Maximum Flefeet® spacing (axial dimension):
 - Maximum Elefeet® spacing (axial dimension): 600 x 600 mm

Note:

The detailed solution shown here refers mainly to the ZinCo System Build-up. The roof construction itself as well as any other constructions are shown schematically and must be planned according to the relevant standards and guidelines.

Project:

.

Version: 15.01.2019 JGI/ EVo

Scale: none Size:

Α3

Wa02_G+F_Elef_Fd.dwg

Authorized by ZinCo GmbH, Lise-Meitner-Str. 2, 72622 Nuertingen/ Germany; Tel: ++49/7022-6003-0 info@zinco-greenroof.com; www.zinco-greenroof.com



Subject to technical alterations and printing errors.